

# Choosing the Right Charging Solution

A diverse group of people of various ages and ethnicities are posed around a dark grey charging station. From left to right: a young woman with long dark hair in a white tank top and jeans; a young girl in a green hoodie and jeans sitting on the station and blowing bubbles; a woman in an orange sleeveless top and skirt; and an older man in a dark blue zip-up jacket and jeans. In the foreground, a man with a beard and tattoos in a light grey t-shirt and dark pants is crouching. The background is a plain, dark grey wall.

Checklist &  
Comparison of Amp5 vs Wallboxes

**AmpSociety**

Charging without compromise

# Checklist

When planning your investment in charging infrastructure, there are several factors that affect operational reliability, total cost over time, and future flexibility.

Below is a checklist to use as support in your decision-making process.

Category	Questions to ask	
<b>Communication &amp; Operational Reliability</b>	Is there a wired network (LAN) to each outlet for reliable connectivity?	<input type="checkbox"/>
	Is there native OCPP support to avoid dependency on manufacturer's cloud service?	<input type="checkbox"/>
	Is there support for OCPP 2.0.1 for future services like Plug&Charge and V2G?	<input type="checkbox"/>
	Does the system have automatic recovery functions to avoid site visits during operational disruptions?	<input type="checkbox"/>
<b>Power Optimization &amp; Safety</b>	Can the system dynamically balance phases and distribute current to optimize available power?	<input type="checkbox"/>
	Does each charging outlet have a self-resetting residual current device and fuse? Or are site visits required for reset?	<input type="checkbox"/>
	Is surge protection included to protect vehicles and the facility? (Legal requirement for public charging).	<input type="checkbox"/>
	Can the system be integrated with the building's safety system (e.g. emergency stop on fire alarm)?	<input type="checkbox"/>
<b>User Experience &amp; Operations</b>	Is there a display showing charging status, error codes, and dynamic QR codes for secure payment?	<input type="checkbox"/>
	Does the system have a battery backup to unlock charging in the event of a power outage?	<input type="checkbox"/>
	Can lighting be integrated for increased safety and comfort in the parking area?	<input type="checkbox"/>
<b>Installation &amp; Future Scalability</b>	Is the installation modularized and quality-assured, or dependent on 3 <sup>rd</sup> party installation materials?	<input type="checkbox"/>
	Can the facility be expanded without new groundwork and cable routing?	<input type="checkbox"/>
	Can the same infrastructure also be used for other needs, e.g., engine block heaters?	<input type="checkbox"/>

# Wallbox or System Solution?

Different projects require different solutions. We believe wallboxes should be used in smaller installations or where site-specific conditions do not allow a system solution.

However, for larger installations, it is important to consider functionality that meets requirements for operational reliability, total cost over time, easy expansion, and future-proof features.

In the tables below, we compare Amp5 with two commonly used wallboxes<sup>1</sup>. The purpose is not to disparage these products, but to clarify what advantages Amp5 can offer in larger and more business-critical installations.

## Communication & Operational Reliability

Feature	Amp5	Zaptec Pro	CTEK CC3
<b>Redundant LAN</b>	Yes, each outlet has redundant wired LAN for internet connectivity. This minimizes the risk of communication disruptions.	No, primarily uses wireless connectivity.	Yes, LAN but no redundancy.
<b>Direct OCPP</b>	Yes, Amp5 supports OCPP 1.6J and 2.0.1 (without proxy).  Amp5 communicates directly with the charge operator's backend. This eliminates dependency on the hardware manufacturer's cloud service.  OCPP 2.0.1 enables future services such as Plug&Charge and V2G.	No, only OCPP 1.6J via Zaptec's own cloud (proxy).	Yes, for OCPP 1.6J.  OCPP 2.0.1 support has been communicated in product roadmap.
<b>Self-healing System</b>	Yes, Amp5 has a built-in function that monitors operations and internet connectivity. In case of disruption, automatic restart occurs at processor level and active charging sessions are paused and then resumed.	No, only automatic in connection with firmware updates. Manual restart (soft reset) possible remotely.	No, only automatic in connection with firmware updates. Manual restart (soft reset) possible remotely.

<sup>1</sup> Based on publicly available data.

## Power Optimization & Safety

Feature	Amp5	Zaptec Pro	CTEK CC3
<b>Load Balancing via LAN at Multiple Levels</b>	Yes, via LAN. Support for RS485-connected energy meter (Modbus) at service level.	No, only via PLC.	Yes, via LAN.
<b>Phase Switching/Current Allocation for optimization of available capacity</b>	Yes, support for dynamically switching phases and distributing current between phases depending on EV needs.	Yes, support for dynamic phase balancing.	No, only static phase allocation.
<b>Self-resetting RCD Type B &amp; Circuit Breaker</b>	Yes, built-in RCD and fuse at each charging outlet.  Both are self-resetting after the charging cable is disconnected, minimizing the need for site visits.	No, only the RCD is self-resetting after disconnecting charging cable.	No, only the RCD is self-resetting after disconnecting charging cable.
<b>Surge Protection against lightning and voltage spikes</b>  Legal requirement for public charging!	Yes, centralized surge protection as standard.	No, requires separate installation.	No, requires separate installation.
<b>Emergency Stop</b>	Amp5 has an input for emergency stop that can be integrated with the building's existing fire or safety system.  On alarm, all charging sessions are immediately interrupted.	No, only possible via separate installation.	No, only possible via separate installation.




# AmpSociety

Charging without compromise

## User Experience & Operations

Feature	Amp5	Zaptec Pro	CTEK CC3
<b>Display</b>	Amp5 is equipped with a 4.3" TFT display that can show real-time charging data, error messages, and digital QR codes.  Digital QR codes prevent fraud with fake stickers.	No, lacks display.  MID version only has a counter for kWh.	No display on standard CC3. The CC3i variant has a 7" touchscreen with dynamic QR codes and real-time charging data.
<b>Battery Backup</b>	Amp5 has integrated battery backup that allows ongoing charging sessions to be safely concluded during power outages and charging outlets to be unlocked. System owners are notified automatically.	No backup function.  Requires separate installation.	No backup function.  Requires separate installation.
<b>LED Lighting</b>	Amp5 can be delivered with integrated LED lighting for increased safety and comfort in parking areas.	No, lacks this feature.	No, lacks this feature.



# AmpSociety

Charging without compromise

## Installation & Scalability

Feature	Amp5	Zaptec Pro	CTEK CC3
<b>Modular Installation</b>	Amp5 is a fully modularized system where every module and installation is predetermined. This ensures the highest quality and eliminates the risk of faulty workmanship or substandard components.  Additionally, installation time is minimized.	No, needs to be supplemented with third-party materials during installation.	No, needs to be supplemented with third-party materials during installation.
<b>Ground Expansion</b>	Amp5 is built on ground screws or pole bases with integrated cabling. Expansion can be done quickly and without costly groundwork or new cable routing.	No, requires new groundwork and cable routing for expansion.	No, requires new groundwork and cable routing for expansion.
<b>Engine Block Heaters</b>	Amp5 can also be used for engine block heaters via EVSE adapter thanks to phase switching support. This provides more use cases for the same infrastructure.	No, warranty covers EV charging only. EVSE adapters may not be used unless approved by the vehicle manufacturer.	No, warranty covers EV charging only. EVSE adapters are not permitted according to the manual.



Centralized charging technology for operational reliability.




Modular for fast & reliable installation.

# Aesthetics

---

Naturally a matter of taste, but many Amp5 customers appreciate the discreet design, especially for larger installations. Below are a few customer references.

## Slottsmöllan, Halmstad in Sweden



# Aesthetics

Wihlborgs Properties, Malmö in Sweden



**AmpSociety**  
Charging without compromise

# Aesthetics

Stena Properties, Malmö in Sweden



**AmpSociety**  
Charging without compromise

# Amp5 - Technical Information

<b>Max number of charging outlets</b>	54 per Smart Hub <sup>1</sup>	<b>Display</b>	TFT 480x272px, (HxW): 55 x 96 mm
<b>Max number of simultaneous charging sessions</b>	30 per SmartHub <sup>1</sup>	<b>Temperature range - operating</b>	-30°C to 45°C air temp.
<b>Max incoming current</b>	63A per SmartHub <sup>1</sup>	<b>Temperature range - non-operating</b>	-30°C to 65°C condensation-free
<b>Max simultaneous charging power</b>	44kW	<b>Material</b>	Aluminum, minimum 75% recycled aluminum
<b>Max charging power per outlet</b>	22kW (3-phase), 7.4kW (1-phase)	<b>Color</b>	Graphiteblack (RAL 9011), powder-coated
<b>Main fuse</b>	63A, B-characteristic	<b>Lock</b>	EBR-lock "Stockholm"
<b>Communication protocol</b>	OCPP 1.6J / OCPP 2.0.1 / ISO15118-20	<b>IP rating</b>	IP54
<b>Network connection</b>	Teltonika RUT 901 with 4G SIM card LAN Wifi (configuration only)	<b>IK rating</b>	IK10
<b>RF technology</b>	GSM, GPRS, EDGE, UMTS/HSPA+, LTE	<b>Auto charge</b>	ISO15118-2:MAC
<b>RFID type</b>	ISO/IEC 14443 Type A, 13.56 MHz Mifare	<b>Other</b>	Customizable display content via OCPP  RCD testing with magnetic sensor  User interaction via QR code, RFID  Lockable charging outlets
<b>Current measurement</b>	MID certified version of Amp5 is available for delivery in May 2026.		
<b>24V input for external switch</b>	Yes		
<b>Static load balancing against fixed value</b>	Yes		
<b>Dynamic load balancing</b>	Yes. Via internet or locally with Modbus TCP / RS-485		
<b>Residual current device</b>	Type B per outlet (IEC60947-2)		
<b>Circuit breaker</b>	32A B-characteristic		
<b>Battery backup (UPS)</b>	Capacitor		
<b>Charging outlet</b>	Typ 2, (IEC 62196-2)		

<sup>1</sup> If more than 54 charging outlets, more simultaneous charging sessions, or support for higher incoming current is desired, Amp5 is supplemented with additional SmartHubs.

